



Maura Healey, Governor
Kimberley Driscoll, Lieutenant Governor
Phillip Eng, Interim MassDOT Secretary
Jonathan L. Gulliver, Undersecretary and Highway Administrator



October 16, 2026

612874-136561

ADDENDUM NO. 5

To Prospective Bidders and Others on:

SHREWSBURY-WORCESTER
Bridge Preservation, S-14-021=W-44-115, I-290 (EB and WB)
over Lake Quinsigamond and Lake Avenue North

THIS PROPOSAL TO BE OPENED AND READ: TUESDAY, OCTOBER 27, 2026 at 2:00 P.M.

Transmitting revisions to the Contract Documents as follows:

DOCUMENT 00715: Revised page 21.

Take note of the above, substitute the revised page for the original, and acknowledge Addendum No. 5 in your Expedite Proposal file before submitting your bid.

Very truly yours,

Slava
Podluzny
for y
Eric M. Cardone, P.E.
Construction Contracts Engineer

Digitally signed
by Slava
Podluzny
Date: 2026.10.16
10:52:34 -04'00'

HA
cc: Genesis PozDiaz, Project Manager

THIS PAGE IS INTENTIONALLY LEFT BLANK



- The Device Feed shall be public or use “Basic” HTTP Authentication.
- The Device Feed shall be provided over HTTPS.
- The Device Feed shall reflect changes in CWZNS field device status (e.g., display changed or device moved) no later than 60 seconds after they occur.
- For each CWZNS field device, the “update date” property shall be no older than 60 minutes, except when it has stopped communicating or is otherwise in error.
- The “id” property of each CWZNS field device feature in the Device Feed shall stay the same for the duration of the Contract and shall be a Universally Unique Identifier (UUID) to guarantee uniqueness between feeds and over time.

M10.18.1: Location Marker

Location Markers shall meet the requirements of M10.18.0: Connected Work Zone Notification System Devices.

Location Markers may be standalone devices or an attachment to a channelizing device. Either type shall be certified to comply with the relevant minimum TL-3 testing requirements of the *Manual on Assessing Safety Hardware*.

⑤ **M10.18.2: Connected Arrow Board**

Connected Arrow Boards shall meet the requirements of M10.18.0: Connected Work Zone Notification System Devices.

A Connected Arrow Board shall be capable of transmitting its location, verifying the time and location of an event.

Connected Arrow Boards shall be capable of transmitting their display status.

Arrow Boards may be connected to meet these specifications either through a retrofit kit or an appurtenance that is integral to the Arrow Board.

[illegible]

END OF SUPPLEMENTAL SPECIFICATIONS